

CT2404L 电流互感器
CT2404L Current Transformer


产品特点 Features

- ◆ PBT 外壳, 耐高温, 耐腐蚀, 隔离性能好, 抗冲击性强; PBT case-resistance to high temperature and corrosion, risen-perfect isolation and resistance to strong impact;
- ◆ 体积小, 外形美观, 安装方便; Small in size and pleasant to eyes easy installation;
- ◆ 线性好, 精度高, 线性范围宽, 一致性好。Excellent linearity and isolation, high precision, wide in linearity range and overall consistency;
- ◆ 用于进行电量采集及对电量的监测; Used for the electric quantity collection and power monitoring;
- ◆ 产品符合 UL 认证标准, UL 号 E535782。The product meets UL certification standards with UL number E535782.

主要技术参数 Main parameters

型号 Model	额定输入/输出 Rated input/output	准确级 Accuracy	绝缘电阻 Insulation resistance	角差 Angle difference	负载电阻 Load resistance	隔离耐压 Isolated withstand voltage	穿线孔径 Threading aperture
CT2404L-5k-50	50A/10mA	0.2、0.2S	≥500Mohm	≤10'	≤20Ω	4.0kV	Φ16mm 24.5×4mm
CT2404L-5k-100	100A/20mA						
CT2404L-5k-150	150A/30mA						
CT2404L-5k-200	200A/40mA						

产品规格 (尺寸单位: mm) Specification (Dimension unit: mm)




UL 认证标识如下:

The UL certification mark is as follows:



安装方式 Installation



互感器用螺钉固定在铜排上。

The transformer is fixed to the copper busbar with screws.

说明 Note:

- 工作温度 Operating temperature: -25℃~75℃; 贮存温度 Storage temperature: -40℃~75℃;
- 相对湿度 Relative humidity: 10%~95%RH;
- 上表所列为常用规格, 还可根据客户要求另行设计。The products are customized according to user's requirements.

注：以上图片仅供参考，产品以实物为准。

Note: The above pictures are for reference only, the products are subject to the actual product, 版权所有，保留一切权利。内容如有改动，恕不另行通知。

Copyright, all rights reserved. Specification subject to change without prior notice.